

The table below details the specifications for every product in the Guard load arrestor range.

Name	Product Code	Maximum Working Load		Rope Length		Rope & Shackle Material	Minimum Anchor Strength		Maximum Running Speed	
		kg	lb	m	ft		kN	lbf	m s <sup>-1</sup>	ft s <sup>-1</sup>
GUARD150	GSE150-14G	150	330	14	46	Galvanised Steel	7.4	1,663	1	3.280
	GSE150-14S	150	330	14	46	Stainless Steel	7.4	1,663	1	3.280
GUARD300	GSE300-10G	300	660	10	33	Galvanised Steel	14.1	3,169	0.7	2.297
	GSE300-10S	300	660	10	33	Stainless Steel	14.1	3,169	0.7	2.297
	GSE300-25G	300	660	25	82	Galvanised Steel	14.1	3,169	0.7	2.297
	GSE300-25S	300	660	25	82	Stainless Steel	14.1	3,169	0.7	2.297
GUARD500	GSE500-10S	500	1,100	10	33	Stainless Steel	20.6	4,631	0.7	2.297
	GSE500-24S	500	1,100	24	79	Stainless Steel	20.6	4,631	0.7	2.297
	GSE500-10G	500	1,100	10	33	Galvanised Steel	20.6	4,631	0.7	2.297
	GSE500-24G	500	1,100	24	79	Galvanised Steel	20.6	4,631	0.7	2.297
GUARD800	GSE800-10S	800	1,760	10	33	Stainless Steel	45.1	10,123	0.6	1.969
GUARD1000	GSE1000-10G	1000	2,200	10	33	Galvanised Steel	45.1	10,123	0.6	1.969
GUARD1500	GSE1500-10G	1500	3,300	10	33	Galvanised Steel	63.3	14,230	0.6	1.969

